

Flex-S3 Cable Accessories for Single Microinverter System



Flex-S3 Field Connector

The Flex-S3 Field Connector is used when a PV system has only one microinverter. It helps make a quick and simple connection between the microinverter and the electrical grid.



Flex-S3 Plug and Play Cable-CEE7/7

The Flex-S3 Plug and Play Cable-CEE7/7 is designed for the situation where a PV system has only one microinverter. It includes a Flex-S3 Field Connector, an AC cable, and a plug. The Flex-S3 Field Connector attaches to the microinverter, and the plug connects to a household socket, following local regulations.

This simple design lets you quickly and easily connect the system to the grid.



Technical Specifications

•				
Flex-S3 Field Connector				
Compatible microinverter	HMS series			
Pin number	2P+PE			
Rated voltage	300 V			
Rated current	12 A (Use 1.5 mm² copper cable)			
Applicable cable specification	1.0/1.5 mm ²			
Applicable cable outer diameter	8 to 9.5 mm			
Cable connection type	Screw pressing			
Ambient temperature range	-40°C to +85°C			
Dimensions (L \times W \times H)	135 × 38 × 25 mm			
Protection degree	IP68			
Flame resistance degree	UL 94-V0			
Compliance	RoHS			
Product standard	PPP 59015A: 2013			
Flex-S3 Plug and Play Cable-CEE7/7				
Compatible microinverter	HMS series			
Consisting components	Flex-S3 Field Connector + Cable + AC plug			
Cable type	PV07AC-F			
Conductors cross-sectional area	1.5 mm²			
Cable outer diameter	9.3±0.40 mm			
Minimum bending radius	5 cm			
AC Plug standard	CEE 7/7			
Rated voltage	250 V			
Rated current	12 A			
Ambient temperature range	-40°C to +85°C			
Compliance	RoHS			

Ordering Options

Product standard

Name	New Model (Previous Model)*	Cable Length Between Connector and Plug	Number per Box	Box Dimensions
Flex-S3 Field Connector	S3-FC-EN15S (HMS Field Connector-1PCS)		300 PCS	495 × 290 × 255 mm
	S3-FC-EN15S(100PCS) (HMS Field Connector-100PCS)	1	3 PCS	
	S3-FC-EN15C (HMS Field Connector-EN15C-100PCS)		3 PCS	
Flex-S3 Plug and Play Cable-CEE7/7	S3-PPC7-EN15-300 (HMS Plug and Play Cable-CEE7/7-3m)	3.0 m	30 PCS	345 × 345 × 375 mm
	S3-PPC7-EN15-500 (HMS Plug and Play Cable-CEE7/7-5m)	5.0 m	20 PCS	345 × 345 × 375 mm
	S3-PPC7-EN15-1000	10.0 m	10 PCS	345 × 345 × 375 mm

PPP 59015A: 2013 (Connector) / TÜV 2 PfG 1940 (Cable) / VDE 0620 (Plug)

^{*:} Hoymiles has renamed the accessories listed above, and that's the only change we've made. Please be assured that everything else remains the same.